


Operating and maintenance instructions

BLÜCHER Industrial® floor drains in stainless steel



Comprising:

Drains type nos.: 711, 712, 713, 714, 715, 726, 743, 760, 761, 763, 766, 767, 769, 771, 774 and 775

Water traps type nos: 502 and 562

Filter basket type no: 780

3 mm grating 168x168, 268x268, OD173 and OD273

Annular grating 168x168, 268x268, OD173 and OD273

Mesh grating 168x168, 268x268, OD173 and OD273

Ladder grating 168x168, 268x268, OD173 and OD273

Cast grating 168x168, 268x268, OD173 and OD273



For the owner:

BLÜCHER Industrial® floor drain in stainless steel AISI 316L or optionally AISI 304 has been installed. The floor drain has been approved in accordance with the international standards as to flow capacity and self-cleansing.

Prior to starting use:

- Check that the drain has been cleaned leaving no concrete spills etc.
- Check that the water trap has been installed. If a filter basket is to be included, check also that this has been installed.
- In flexible sheet floors check that the clamping ring has been properly fixed.
- Check that the type of grating chosen is suitable for the weight load required.

Normal operation:

BLÜCHER Industrial® floor drain in stainless steel has a removable water trap with excellent self-cleansing capabilities. In case of many impurities it may be necessary to clean the water trap at appropriate intervals.

Cleaning:

- Remove grating, filter basket and water trap.
- Clean water trap, filter basket and grating with detergent as necessary.
Make sure that lubricant has been applied to the sealing ring of the water trap. Install the water trap applying a light pressure and twisting the water trap down to the stop ring in the drain. To avoid bad odours, make sure that the sealing ring of the water trap fits tightly to the drain.
- Replace filter basket and grating.

Technical data:

Specification of the product range and technical information are available as catalogues.

BLÜCHER

Pugdølvej 1 . DK-7480 Vildbjerg . Denmark

Tlf. +45 99 92 08 00 . Fax +45 99 92 08 30

www.blucher.com . mail@blucher.dk