

BLÜCHER® **Plug & Play Penetration**

Installation instruction

Montagevejledning



BLÜCHER®

A **WATTS** Brand





1

UK Ensure that the sealing surface is clean.

DK Pakfladen aftørres.



2

UK Mount the penetration.

DK Monter gennemføringen.



3

UK Center in hole.

DK Centrér i hullet.



4

UK Tighten the bolts.

DK Spænd boltene.



5

UK Tighten bolts in cross order with torque wrench to torque 12Nm.

DK Boltene krydsspændes moment-nøgle til moment 12Nm.



- For decks 4 - 15 mm thickness
- Max. unevenness of 3 mm (weld seam)

Type no.	D	Cut out Recommended +6/-2 mm	Cut out Min./Max.
868.910.050	50	Ø118 mm	Ø116/124 mm
868.910.075	75	Ø142 mm	Ø140/148 mm
868.910.110	110	Ø184 mm	Ø182/190 mm
868 910.125	125	Ø193 mm	Ø191/199 mm
868 910.160	160	Ø228 mm	Ø226/234 mm

Bolt størrelse Bolt size	Moment Torque setting
M8	12Nm

BLÜCHER® Drain

BLÜCHER® Channel

BLÜCHER® EuroPipe

BLÜCHER®

A WATTS Brand

Tel.: +45 99 92 08 00 · marine@blucher.com · www.blucher-marine.com

© 2020 www.marine-blucher.com